



Quantum Timber Finishes Product Data Sheet

MicroFloor



- Description:** MICROFLOOR IS A PREMIUM TANNIN RESISTANT CLEAR URETHANE. MICROFLOOR IS A SINGLE PACK HARDWEARING TANNIN BLOCKING CLEAR, FAST DRYING COATING WITH A VERY SMOOTH FLOW AND SELF LEVELLING FINISH. IT IS TINTABLE, NON TOXIC, LOW ODOUR AND V.O.C. COMPLIANT.
- Where to use:** Suitable for most prepared timber flooring.
- Application:** Timber surfaces must be fresh and free of grease dust and contaminants. Remove old coating using a 180 grit paper. Remove sanding residue. Apply by brush, short nap (8-10mm) roller. MicroFloor causes very little grain raising on most woods. MicroFloor is fast drying, touch dry within 30 minutes; hence multiple coats per day are possible. Two hour drying time between coats is advised. Avoid using above 30 °C and below 14°C. Sanding after the first coat will give a sound smooth base for remaining coats. A minimum of 3 more coats is advised. After curing has taken place, surfaces may be cleaned with mild detergent and water. Stir MicroFloor thoroughly with a flat stirrer for at least 1 minute. Do not shake.
- Coverage:** 10-12 square metres per litre for the first coat. Further coats can achieve up to 16 sq. m. per litre.
- Drying Time:** MicroFloor is fast drying, touch dry in 30 minutes at 25°C with 50% relative humidity. It may be recoated after two hours and will accept light traffic after 16 hours. It will accept normal traffic after three days. Full hardness and cure may take 30 days. During this time avoid dragging furniture and use protection under legs of furniture. Care should be taken with new surfaces.
- Tinting:** MicroFloor can be tinted with machine tints or transparent tints, or as an overcoat to Quantum Aquastain Colours.
- Environmental:** Non toxic. Non flammable. Quantum Timber Finishes do not use mineral spirit products in manufacturing; hence all Quantum products are low in VOCs.
VOC <135g/litre
The entire range is free of hazardous air pollutants (HAPS).
- Disposal:** Do not pour left-over product down drains. Dispose of with regard to appropriate local council regulations.
- Clean up:** Wash brushes and tools in soap and water.

KEEP OUT OF REACH OF CHILDREN. If swallowed, do not induce vomiting, call nearest poisons information centre. Keep away from flame and heat.

Ph: 03 9776 8831

Fax: 03 9782 4417

Freecall: 1800 053 018

quantum@qtf.com.au